





We are one of the specialist in manufacturing of :
Full range of  marked fire extinguishers

→ POWDER

→ CARBON DIOXIDE

→ MECHANICAL FOAM

→ WATER Co2

→ CLEAN AGENT





DRY POWDER STORES PRESSURE TYPE

**BEST USAGE AT : HOMES . OFFICE . BUILDINGS
WAREHOUSES . FARMS ETC.**

Technical Specification

ABC Stored pressure Type Fire Extinguisher

MODEL	RSP1	RSP2	RSP4	RSP6	RSP9
Capacity	1 Kg	2 Kg	4 Kg	6 Kg	9 Kg
Confirming IS No.	15683	15683	15683	15683	15683
Fire Rating	1A, 8B	1A, 13B	2A, 21B	3A, 34B	3A, 34B
Operating Temperature	-20° c to +55° c	-20° c to +55° c	-20° c to +55° c	-20° c to +55° c	-20° c to +55° c
Min. Jet Length (in Mtrs.)	2 Mtrs.	2 Mtrs.	2 Mtrs.	2 Mtrs.	2 Mtrs.
Discharge Percentage Min.	85%	85%	85%	85%	85%
Discharge Time Min.	8 Sec.	13 Sec.	13 Sec.	13 Sec.	13 Sec.
Charge Pressure	15Kgf/cm ²	15Kgf/cm ²	15Kgf/cm ²	15Kgf/cm ²	15Kgf/cm ²
Test Pressure	35Kgf/cm ²	35Kgf/cm ²	35Kgf/cm ²	35Kgf/cm ²	35Kgf/cm ²
Operating Valves	Squeeze Grip Type	Squeeze Grip Type	Squeeze Grip Type	Squeeze Grip Type	Squeeze Grip Type
Extinguisher Media	Dry Powder 14609 (map)	Dry Powder 14609 (map)	Dry Powder 14609 (map)	Dry Powder 14609 (map)	Dry Powder 14609 (map)
Propellant	Dry Nitrogen	Dry Nitrogen	Dry Nitrogen	Dry Nitrogen	Dry Nitrogen
Anti Corrosive Treatment	Phosphating (7 Tanks)	Phosphating (7 Tanks)	Phosphating (7 Tanks)	Phosphating (7 Tanks)	Phosphating (7 Tanks)
Painting	Exopy Polyester Pow. Coat	Exopy Polyester Pow. Coat	Exopy Polyester Pow. Coat	Exopy Polyester Pow. Coat	Exopy Polyester Pow. Coat
Tare Weight	1 KG	1.4 KGS	2.3 KGS	3 KGS	5.1 KGS
Gross Weight	2 KGS	3.4 KGS	6.3 KGS	9 KGS	14.1 KGS

DRY POWDER CARTRIDGE TYPE

**BEST USAGE AT : HOMES • OFFICE • BUILDINGS
WAREHOUSES • FARMS ETC.**

Technical Specification

BC Cartridge Type Fire Extinguisher



MODEL	RCBC 6	RCBC 9	RCBC 4
Capacity	1 Kg	9 Kg	4 Kg
Confirming IS No.	15683	15683	15683
Fire Rating	34B	89B	21B
Operating Temperature	-20° c to +55° c	-20° c to +55° c	-20° c to +55° c
Min. Jet Length (in Mtrs.)	2 Mtrs.	2 Mtrs.	2 Mtrs.
Discharge Percentage Min.	85%	85%	85%
Discharge Time Min.	8 Sec.	13 Sec.	13 Sec.
Charge Pressure	15Kgf/cm ²	15Kgf/cm ²	15Kgf/cm ²
Test Pressure	35Kgf/cm ²	35Kgf/cm ²	35Kgf/cm ²
Operating Valves	Squeeze Grip Type	Squeeze Grip Type	Squeeze Grip Type
Extinguisher Media	Dry Powder 4308 (SBC)	Dry Powder 4308 (SBC)	Dry Powder 4308 (SBC)
Propellant	Co2 Cartridge	Co2 Cartridge	Co2 Cartridge
Anti Corrosive Treatment	Phosphating (7 Tanks)	Phosphating (7 Tanks)	Phosphating (7 Tanks)
Painting	Exopy Polyester Pow. Coat	Exopy Polyester Pow. Coat	Exopy Polyester Pow. Coat
Tare Weight	4.6 KGS	7.3 KGS	3.6 KGS
Gross Weight	10.6 KGS	16.3 KGS	7.6 KGS



CARBON DIOXIDE FIRE EXTINGUISHER

BEST USAGE AT : CHEMICAL PLANT • OIL RIGS
RAIL YARDS • AIRPORT • ELECTRICAL SUBSTATION
LABORATORISE

Technical Specification Co2 Type Fire Extinguisher

MODEL	RCO2 2	RCO2 4.5	RCO2 3.2
Capacity	2 Kg	4.5 Kg	3.2 Kg
Confirming IS No.	15683	15683	15683
Fire Rating	88	21B	21B
Operating Temperature	-20° c to +55° c	-20° c to +55° c	-20° c to +55° c
Min. Jet Length (in Mtrs.)	2 Mtrs.	2 Mtrs.	2 Mtrs.
Discharge Percentage Min.	85%	85%	85%
Discharge Time Min.	8 Sec.	8 Sec.	8 Sec.
Test Pressure	250Kgf/cm ²	250Kgf/cm ²	250Kgf/cm ²
Operating Valves	Wheel Type	wheel Type	Wheel Type
Extinguisher Media	Co2 Gas IS: 155222	Co2 Gas IS: 15222	Squeeze Grip Type
Propellant	Carbon Di Oxide	Carbon Di Oxide	Carbon Di Oxide
Painting	Enamel Paint Is : 5 Shade 536/538	Enamel Paint IS: 5 Shade 536/538	Enamel Paint IS: 5 Shade 536/538
Tare Weight	6.2 KGS	11.5 KGS	9.5 KGS
Gross Weight	8.2 KGS	16.00 KGS	12.5 KGS



CLEAN AGENT FIRE EXTINGUISHER

BEST USAGE AT: COMPUTERS • AIRCRAFT • BOATS
OFFICE • LABORATORIES • TELEPHONE ETC.

Technical Specification Clean Agent Fire Extinguisher

MODEL	RCA2	RCA4	RCA 6
Capacity	2 Kg	4 Kg	6 Kg
Confirming IS No.	15683	15683	15683
Fire Rating	1A, 88	1A, 138	1A, 218
Operating Temperature	-20° c to +55° c	-20° c to +55° c	-20° c to +55° c
Min. Jet Length (in Mtrs.)	2 Mtrs.	2 Mtrs.	2 Mtrs.
Discharge Percentage Min.	85%	85%	85%
Discharge Time Min.	13 Sec.	13 Sec.	13 Sec.
Charge Pressure	15Kgf/cm ²	15Kgf/cm ²	15Kgf/cm ²
Test Pressure	35Kgf/cm ²	35Kgf/cm ²	35Kgf/cm ²
Operating Valves	Squeeze Grip Type	Squeeze Grip Type	Squeeze Grip Type
Extinguisher Media	HFC 236fa	HFC 236fa	HFC 236fa
Propellant	Dry Nitrogen	Dry Nitrogen	Dry Nitrogen
Anti Corrosive Treatment	Phosphating (7 Tanks)	Phosphating (7 Tanks)	Phosphating (7 Tanks)
Painting	Exopy Polyester Pow. Coat.	Exopy Polyester Pow. Coat	Exopy Polyester Pow. Coat
Tare Weight	1.4 KGS	2.3 KGS	3 KGS
Gross Weight	8.2 KGS	6.3 KGS	9 KGS



WATER TYPE STORED PRESSURE FIRE EXTINGUISHER

BEST USAGE AT :

PAPER • WOOD • COTTON • SCHOOL • THEATERS

Technical Specification

Water Type (S/P) Fire Extinguisher & Cartridge Type

MODEL	RSPW 9	RSW 9
Capacity	9 Kg	9 Ltr.
Confirming IS No.	15683	15683
Fire Rating	4A	4A
Operating Temperature	-5° c to +55° c	-5° c to +55° c
Min. Jet Length (in Mtrs.)	2 Mtrs.	2 Mtrs.
Discharge Percentage Min.	85%	85%
Discharge Time Min.	13 Sec.	13 Sec.
Charge Pressure	15Kgf/cm ²	15Kgf/cm ²
Test Pressure	35kgf/cm ²	35kgf/cm ²
Operating Valves	Co2 Gas IS: 155222	Squeeze Grip Type
Extinguisher Media	Water	Water
Propellant	Dry Nigogent	Dry Nigogent
Anti Corrosive Treatment	Phosphating (7 Tanks)	Phosphating (7 Tanks)
Painting	Epoxy Polyester Powder Coating	Epoxy Polyester Powder Coating
Tare Weight	4KGS	7.5 KGS
Gross Weight	13 KGS	16.3 KGS



MECHANICAL FOAM (S/P) FIRE EXTINGUISHER

BEST USAGE AT: PETROLEUM PRODUCT. PAINT

PIGMENT AND VARNISH . PAPER . WOOD . COTTN

Technical Specification

Mechanical Form (s/p) Fire extinguisher & Cartridge Type

MODEL	RSPM9	RCM9
Capacity	9 Ltr.	9 Kg
Confirming IS No.	15683	15683
Fire Rating	4A, 898	1A, 138
Operating Temperature	-5° c to +55° c	-5° c to +55° c
Min. Jet Length (in Mtrs.)	2 Mtrs.	2 Mtrs.
Discharge Percentage Min.	85%	85%
Discharge Time Min.	13 Sec.	13 Sec.
Charge Pressure	15Kgf/cm ²	15Kgf/cm ²
Test Pressure	35Kgf/cm ²	35Kgf/cm ²
Operating Valves	Squeeze Grip Type	Squeeze Grip Type
Extinguisher Media	HFC 236fa	AFFF IS: 4989
Propellant	Dry Nitrogen	Dry Nitrogen
Anti Corrosive Treatment	Phosphating (7 Tanks)	Phosphating (7 Tanks)
Painting	Exopy Polyester Pow. Coat.	Epoxy Polyester Powder Coating
Tare Weight	4 KGS	4 KGS
Gross Weight	13 KGS	13 KGS



TROLLEY MOUNTED TYPE FIRE EXTINGUISHER



**WATERCO2
50Ltr.**



**MECHANICAL FORM
50Ltr.**



**MECHANICAL FORM
150Ltr.**



DCP 25 kg.



DCP 50 kg.



DCP 75 kg.

DRY POWDER / CLEN AGENT MODULAR TYPE FIR EXTINGUISHER



2 KG



5 KG



10 KG



15 KG



HYDRANT SYSTEM ACCESSORIES



ESSBEE FIRE SERVICES PVT. LTD.

AN ISO 9001 : 2008 CERTIFIED CO.

Road No. 07, Maharaja Shri Agrasenji, Chowk (Ganghi chowk), Prabhat Colony,
Santacruz (East), Mumbai - 400 055,

Tel.: +91 93222 12299 / 93214 44963 / 022 6953 2745 / 022 6953 2751

www.essbeeservices.com / Email : info@essbeeservices.com / balya1973@gmail.com